

## General technical data


	Unit	CrystalLed™ 24	CrystalLed™ 48	CrystalLed™ 72	CrystalLed™ 96
Total Lumens output (6000°K)	Lumen [lm]	3711	7423	11134	2240
LED Type		Cree XT-E	Cree XT-E	Cree XT-E	Cree XT-E
Number of LEDs	#	24	48	72	96
Color temperature	Kelvin [K]	3000, 4500, 6000	3000, 4500, 6000	3000, 4500, 6000	3000, 4500, 6000
Dimensions (LxWxH)	[mm]	127 x 215 x 105	227 x 215 x 105	327 x 215 x 105	427 x 215 x 105
Weight (light engine only)	kilogram [kg]	1,1	1,9	2,7	3,4
Ingress Protection	[IP]	65 / 67	65 / 67	65 / 67	65 / 67
Operating temperature	[°C]	-40 / +80	-40 / +80	-40 / +80	-40 / +70

## With 450 mA driver

		CrystalLed™ 24	CrystalLed™ 48	CrystalLed™ 72
Input voltage	Volt [VAC]	190 - 265	190 - 265	190 - 265
System power	Watt [W]	39	76	109
Number of LEDs		24	48	72
Total Lumen output (6000°K)	Lumen [lm]	3711	7423	11134
Lumen pr Watt (system)		95,2	97,7	99,4

## With 700 mA driver

		CrystalLed™ 48	CrystalLed™ 72	CrystalLed™ 96
System power	Watt [W]	100	150	200
Input voltage	Volt [VAC]	90 - 305	90 - 305	90 - 305
Total Lumen output (6000°K)	Lumen [lm]	11200	16800	22400
Lumen pr Watt (system)		112	112	112



- Easily installed due to its low weight, flexible mounting options and easy clickon installation system.
- Can be delivered with DALI dimming and operated through wireless communication.

- Does not include any environmentally harmful components nor does the production process emit any harmful emissions.
- Waterproof IP65/67